



NOTE:
ALL DIMENSIONS ARE IN INCHES.
DIMENSIONS IN [] ARE MM.

*BOTTOM RAIL BRACKET CAN BE MOVED
IF NEEDED WITHIN THE RANGE NOTED*

NOTES:

1. EACH RAIL SECTION SHALL HAVE A MINIMUM OF ONE RAIL BRACKET.
2. SPACING CANNOT BE GREATER THAN 8'-0" BETWEEN RAIL BRACKETS.
3. BRACKET LOCATION MUST BE NO CLOSER THAN 8" TO A RAIL SPLICE.
4. SEE DRAWING C-003071 FOR RAIL AND PIT FLOOR REACTIONS.

NOTE:
RAIL LENGTH = PIT DEPTH + TRAVEL
+ CAB I.D. HEIGHT + 4"

TOP RAIL MUST BE BETWEEN
14" AND 90"

Waupaca
ELEVATOR COMPANY™

1726 North Ballard Road
Appleton, WI 54911
Phone: 800-238-8739

ELEVATOR CONTRACTOR:			
JOB NAME:		ORDER NUMBER:	
EXCELEVATOR RMR RAIL LAYOUT & SHEAVE LOCATION			
DRAWN BY:	DATE:	SIGNATURE OF APPROVAL	DWG. NO. C-002828